

Remonumentation of Corners, T. 12 N., R. 44 E.

Chains

At cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over broken glass; original corner stone buried on W. side of post; brass cap marked

T12N
R44E R45E
 $\frac{1}{4}$
S12 | S 7

1961

Place collar of rock around post.

Located on gentle SW. slope.

At the cor. of secs. 1, 6, 7, and 12, on E. bdy. of township, which is mkd. by rhyolite stone, 15x9x7 ins., firmly set, mkd. with 5 grooves on S. and 1 groove on N. face; witnessed by a small scattered mound to the W.

At cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over broken glass, and with original corner stone buried on W. side of post; brass cap marked

T12N
R44E R45E
S 1 | S 6
S12 | S 7

1961

Raise a mound of stone around cor.

Corner is located on SE. slope, 40 lks. dist. N. of dim road in bottom of large draw, draining SW.

At the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on E. bdy. of township, which is marked by a blue limestone, 14x8x6 ins., firmly set, marked $\frac{1}{4}$ on W. face; witnessed by a small mound of stone on the W.

At cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over broken glass, and with original corner stone buried on W. side; brass cap marked

T12N
R44E R45E
 $\frac{1}{4}$
S 1 | S 6

1961