

Remonumentation of Corners, T. 12 N., R. 44 E.

Chains

Place collar of rock around post.

Corner is located on gradual SW. slope, about 2 chs. dist. N. of draw, drains SW. A mine shaft on top of hill, bears SE. about 5 chs. dist. and small tunnel at N. base of hill.

At the cor. of Tps. 12 and 13 N., Rs. 44 and 45 E., which is mkd. by a blue limestone, 15x7x5 ins., firmly set, marked with 6 notches on 4 edges, 44 on SW., 13 on NW., 45 on NE. and 12 on SE. faces; witnessed by a mound of stone, S. of cor.

At cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass; orig. cor. stone buried on E. side of post; brass cap marked

T13N	
R44E	R45E
S36	S31
S 1	S 6
T12N	
1961	

Place collar of rock around post, and enlarge the mound of stone, S. of cor.

Corners is located on a SW. slope, about 1½ chs. N. of deep draw near head, drains W., also about 10 chs. N. of top of high ridge.

From this cor., BIM tellurometer traverse station No. U-59-1, 1961, bears N. 0° 18' W., 2.76 chs. dist.

Remonumentation of Corner on HES No. 48, in
T. 10 N., R. 45 E.

Homestead Entry Survey No. 40, located in unsurveyed secs. 21 and 28, T. 10 N., R. 45 E., Mount Diablo Meridian, was surveyed by John C. Brown, Forest Ranger in 1913.

At cor. No. 1-HES No. 48, which is mkd. by a granite stone, 24x16x5 ins., firmly set, mkd. with a X on top (destroyed), 1 HES 48 on side facing claim; from which

X 1 HES 48, marked on W. side (near SW cor.) of old
lumber cabin, bears S. 78° 39' E., 11 lks dist. No
other accessories.

At cor point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass and a rock, 12x10x2 ins., mkd. X; with orig. cor. stone buried on E. side of post; brass cap marked

HES	
1	
48	
1961	

Place collar of rock around post.

The Meadow Creek Forest Service Guard Station, bears westerly about 10 chs. dist.