

Remonumentation of Corners on HES No. 176, in
T. 11 N., R. 44 E.

Chains

Also witnessed by a mound of stone, 2x1 ft. on the N.

At cor. point,

Set an iron post 30 ins. long, 2½ in. diam., 18 in. in ground to rock, over glass, orig. cor. stone buried on NW. side, mkd

HES 176
3
1961

Raise a mound of stone around post to top.

At cor. No. 4, HES No. 176, marked by a cross (X) on top, with 4 HES 176 on N. face of granite outcrop, 30x4x2 ft.; from which

A granite outcrop, 20x10x10 ft., marked X HES 176 BR., bears N. 15° 06' W., 126 lks. dist.

A granite outcrop, 30x15x3 ft., marked X HES 176 BR., bears N. 51° 46' W., 72 lks. dist.

At cor. point

Set a brass tablet, 3¼ in. diam., 3½ in. stem, cemented in drill hole; marked

HES
4
176
1961

Raise a mound of stone, N. of tablet.

At cor. No. 5 HES No. 176, on sec. line bet. secs. 15 and 22, monumented by a granite stone, 28x9x5 ins., firmly set, marked 5 HES 176 on side facing claim and CC on SE. side; from which

A granite rock, 4x3x2 ft., marked x HES 176 BR., bears S. 82° 49' W., 142 lks. dist.

At cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass, with orig. cor. stone buried on SE. side of post; brass cap marked

5
HES
176
1961

Place collar of rock around, and raise a mound of stone, 2x1½ ft., within claim.

Corner is located 20 lks. dist. of unimproved road bearing N. and SW.

At the ¼ sec. cor. of secs. 15 and 22, T. 11 N., R. 44 E., established by F. C. Haman, Forest Ranger, in 1917, in connection with his survey of HES No. 176, which is monumented by a granite stone, 24x7x7 ins., firmly set, marked ¼ on S. face, and witnessed by a mound of earth and stone, 2x1½ ft. W. of cor.