

TOWNSHIP 25 NORTH, RANGE 56 EAST

CHAINS

These field notes are those of the Remonumentation of certain corners of the Survey Executed by A. J. Hatch and J. C. Smyles, U. S. Deputy Surveyors, in 1872.

Bearings were determined by compass using a magnetic declination of 17° E.

The cor. of secs. 15, 16, 21 and 22, monumented with a squared wooden post, 24 ins. long, 2 ins. square, firmly set in a mound of earth and scribed TXXVN RLVIE SXVI on the NW. face; other marks illegible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N	R56E
<u>S 16</u>	<u>S 15</u>
S 21	S 22

1968

bury the wooden corner post and set an aluminum fence post alongside the iron post.

This cor. is located in dense scrub juniper, none suitable for bearing trees.

The cor. of secs. 28, 29, 32 and 33, monumented with a squared wooden post, 24 ins. long, 2½ ins. square, firmly set in a mound of earth and scribed TXXVN RLVIE SXXXIII on the SE. face; other marks illegible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N	R56E
<u>S 29</u>	<u>S 28</u>
S 32	S 33

1968

bury the wooden corner post and set an aluminum fence post alongside the iron post.

This cor. is located in dense sagebrush, 8.50 chs. E. of a bladed road, bearing N. and S.

The cor. of secs. 5, 6, 7 and 8, monumented with a squared wooden post, 12 ins. long, 1 in. square, set in a mound of earth and stone and scribed TXXVN; all other marks illegible