

TOWNSHIP 25 NORTH, RANGE 56 EAST

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| | |
|-----------|------|
| T25N | R56E |
| S 6 S 5 | |
| S 7 S 8 | |

1968

bury the wooden corner post and set an aluminum fence post alongside the iron post.

This cor. is located on the E. edge of a reseeded area, bearing N. and S.

TOWNSHIP 26 NORTH, RANGE 56 EAST

These field notes are those of the Remonumentation of certain corners of the Survey and Resurvey Executed by Lee G. B. McDowell, U. S. Deputy Surveyor, in 1904.

Bearings were determined by compass using a magnetic declination of 17° E.

The standard cor. of secs. 34 and 35, monumented with a limestone, 16x16x8 ins., firmly set and plainly mkd. with 2 notches on the E. edge, 4 notches on the W. edge and SC on the N. Face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap, 4½ ft. base, with brass cap mkd.

| | |
|-------------|------|
| SC | |
| T26N | R56E |
| S 34 S 35 | |

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

This cor. is located 2.50 chs. W. of a trail road, bearing NNE. and SSW.

The standard ¼ sec. cor. of sec. 34, monumented with a limestone, 18x10x6 ins., firmly set and plainly mkd. SC¼ on the N. face.

The original bearing tree was destroyed by fire.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.