

TOWNSHIP 26 NORTH, RANGE 56 EAST

CHAINS

bury the wooden post and set an aluminum fence post alongside the iron post.

This cor. is located 60 lks. S. of a wash, draining WSW.

The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a limestone, 14x10x4 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on the W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, $3\frac{1}{2}$ ft. base, with brass cap mkd.

T26N R56E

$\frac{1}{4}$
S 34 | S 35

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

This cor. is located 50 lks. N. of a wash, draining SW.

The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with a limestone, 20x14x8 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on the W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.

T26N R56E

$\frac{1}{4}$
S 27 | S 26

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

This cor. is located 40 lks. S. of a draw, draining WSW.

The cor. of secs. 14, 15, 22 and 23, monumented with a limestone, 16x8x6 ins., firmly set in a mound of earth and stone and plainly mkd. with 3 notches on the S. edge and 2 notches on the E. edge.