

TOWNSHIP 26 NORTH, RANGE 56 EAST

CHAINS

T26N R56E
 $\frac{1}{4}$ $\frac{S \ 16}{S \ 21}$

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

No suitable bearing trees available.

This cor. is located 30 lks. S. of a fence, bearing E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a conglomerate stone, 18x10x6 ins., firmly set in a mound of earth and plainly mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R56E
 $\frac{1}{4}$ $\frac{S \ 4}{S \ 9}$

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

This cor. is located on a NW. slope and 2.50 chs. S. of a draw, draining W.

TOWNSHIP 27 NORTH, RANGE 56 EAST

These field notes are those of the Remonumentation of certain corners of the Survey executed by Hatch & Smyles, U. S. Deputy Surveyors, in 1872.

Bearings were determined by compass using a magnetic declination of 17° E.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with a dead juniper tree, 4 ins. diam., firmly set and plainly mkd. X $\frac{1}{4}$.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.