

TOWNSHIP 27 NORTH, RANGE 56 EAST

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T27N	R56E
S 33	S 34
S 4	S 3
T26N	

1968

bury the remains of the wooden post and set an aluminum fence post alongside the iron post.

No other suitable bearing trees available.

This cor. is located 15 lks. N. of a fence, bearing E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented with a limestone, 15x14x8 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T27N	R56E
$\frac{1}{4}$ S 27	
S 34	

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post and raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.

This cor. is located at the corner of a fence, bearing N., S. and W.

The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented with a limestone, 16x10x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the N. face, with a mound of stone N. of cor.

The original bearing trees were destroyed by fire.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T27N	R56E
$\frac{1}{4}$ S 3	
S 10	

1968