

## TOWNSHIP 27 NORTH, RANGE 56 EAST

## CHAINS

The original bearing tree:

A juniper, 20 ins. diam., bears S. 66° E.,  
110 lks. dist., mkd. T27N R56E S11 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins.  
in the ground to underlying stone and in a collar of  
stone, with brass cap mkd.

T27N	R56E
½	
S 11	

1968

bury the mkd. stone and set an aluminum fence post along-  
side the iron post.

No other suitable bearing trees available.

This cor. is located 2.00 chs. S. of a fence, bearing SE.  
and NW.

## TOWNSHIP 29 NORTH, RANGE 56 EAST

These field notes are those of the Remonumentation of  
certain corners of the Survey and Resurvey Executed by  
Lee G. B. McDowell, U. S. Deputy Surveyor, in 1904.

Bearings were determined by compass using a magnetic dec-  
lination of 17° E.

The ¼ sec. cor. of secs. 31 and 36, on the E. bdy. of the  
Tp., monumented with a quartz stone, 18x14x6 ins., firmly  
set and plainly mkd. ¼ on the W. face, with a small mound  
of stone, W. of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T29N	
R56E	R57E
½	
S 36	S 31

1968

bury the mkd. stone and set an aluminum fence post along-  
side the iron post.

This cor. is located at corner of fences, bearing S. and  
W.