

TOWNSHIP 29 NORTH, RANGE 56 EAST

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a quartz stone, 18x10x3 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the W. face, with a small mound of stone, W. of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T29N
R56E R57E
 $\frac{1}{4}$
S 24 | S 19

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

The cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a quartz stone, 20x10x8 ins., firmly set and plainly mkd. with 3 notches on the N. and S. edges, with a small mound of stone, W. of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T29N
R56E R57E
S 13 | S 18
S 24 | S 19

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

This cor. is located on a steep W. slope.

The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a quartz stone, 16x10x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the W. face, with a small mound of stone, W. of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T29N R56E
 $\frac{1}{4}$
S 35 | S 36

1968