

TOWNSHIP 29 NORTH, RANGE 56 EAST

CHAINS

bury the mkd. stone and set an aluminum fence post alongside the iron post.

This cor. is located at corner of fences, bearing N., E. and W.

The cor. of secs. 13, 14, 23 and 24, monumented with a quartz stone, 20x12x8 ins., firmly set and plainly mkd. with 3 notches on the S. edge and 1 notch on the E. edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T29N	R56E
S 14	S 13
S 23	S 24

1968

bury the mkd. stone and set a steel fence post alongside the iron post.

This cor. is located 30 lks. E. of a corner of fences, bearing N., S. and E.

The ¼ sec. cor. of secs. 13 and 24, monumented with a quartz stone, 16x10x10 ins., firmly set and plainly mkd. ¼ on the N. face, with a small mound of stone, N. of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T29N	R56E
¼ S 13	
S 24	

1968

bury the mkd. stone and set an aluminum fence post alongside the iron post.

This cor. is located on a steep W. slope.

TOWNSHIP 37 NORTH, RANGE 61 EAST

These field notes are those of the Remonumentation of certain corners of the Survey Executed by Henry Thurtell, U. S. Deputy Surveyor, in 1900.

Bearings were determined by compass using a magnetic declination of 17½° E.
