

TOWNSHIP 42 NORTH, RANGE 54 EAST, MDM, NEVADA

CHAINS

TOWNSHIP 42 NORTH, RANGE 54 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by H.B. Maxson, U.S. Deputy Surveyor, in 1900.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with a quartzite stone, 17x8x7 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T42N R54E

$\frac{1}{4}$
S 29 | S 28

1975

deposit the original cornerstone alongside the iron post.

This cor. is located in a N-S fence.

The cor. of secs. 20, 21, 28 and 29, monumented with a quartzite stone, 18x14x4 ins., firmly set in a mound of stone, mkd. with 2 notches on the S. edge and 4 notches on the E. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T42N R54E

S 20 | S 21
S 29 | S 28

1975

deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located 3 lks. E. of a N-S fence.

The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with a quartzite stone, 15x8x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on W. face.

At the corner point