

## TOWNSHIP 42 NORTH, RANGE 54 EAST, MDM, NEVADA

## CHAINS

The cor. of secs. 8, 9, 16 and 17, monumented with a quartzite stone, 20x14x8 ins., firmly set in a mound of stone, mkd. with 4 notches on the S. and E. edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T42N R54E	
S 8	S 9
S 17	S 16

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located 3 lks. W. of fence cor., from which fences bear N., E. and S.

The ¼ sec. cor. of secs. 8 and 9, monumented with a quartzite stone, 14x11x3 ins., firmly set in a mound of stone, mkd. ¼ on W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T42N R54E	
¼	
S 8	S 9

1975

deposit the original cornerstone alongside the iron post.

This cor. is located in a N-S fence.

## TOWNSHIP 44 NORTH, RANGE 54 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by Taylor and Keddie, U.S. Deputy Surveyors, in 1902.

The cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a quartzite stone, 18x12x12 ins., firmly set in a mound of stone, mkd. with 2 notches on the S. edge and 4 notches on the N. edge, with a mound of stone W.

At the corner point