

TOWNSHIP 29 NORTH, RANGE 56 EAST, MDM, NEVADA

CHAINS

TOWNSHIP 29 NORTH, RANGE 56 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by L.G.B. McDowell, U.S. Deputy Surveyor, in 1904.

The cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a quartzite stone, 17x10x9 ins., firmly set 12 ins. in the ground, mkd. with 4 notches on S. edge and 2 notches on N. edge, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T29N} \\ \text{R56E R57E} \\ \text{S } 12 | \text{S } 7 \\ \hline \text{S } 13 | \text{S } 18 \end{array}$$

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located 14 lks. S. of an E-W fence.

The ¼ sec. cor. of secs. 12 and 13, monumented with a granite stone, 17x8x8 ins., firmly set 12 ins. in the ground, mkd. ¼ on N. face, with a mound of stone N.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T29N R56E} \\ \frac{1}{4} \frac{\text{S } 12}{\text{S } 13} \end{array}$$

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This cor. is located 3 lks. S. of an E-W fence.

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by A.J. Hatch, J.H. Eaton and J.C. Smyles, U.S. Deputy Surveyors, in 1872 and Resurveyed by L.G.B. McDowell, U.S. Deputy Surveyor, in 1904.

The cor. of secs. 25, 26, 35 and 36, monumented with a quartzite stone, 16x10x10 ins., firmly set 10 ins. in the ground, mkd. with 1 notch on the S. and E. edges, with a mound of stone W.

At the corner point