

TOWNSHIP 30 NORTH, RANGE 57 EAST, MDM, NEVADA

CHAINS

TOWNSHIP 30 NORTH, RANGE 57 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by W.T. Moran, U.S. Deputy Surveyor, in 1890.

The cor. of secs. 20, 21, 28 and 29, monumented with a granite stone, 20x8x8 ins., firmly set 12 ins. in the ground, mkd. with 2 notches on the S. edge and 4 notches on the E. edge, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T30N	R57E
S 20	S 21
S 29	S 28

1975

deposit the original cornerstone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with a quartzite stone, 24x14x6 ins., firmly set 19 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone N.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T30N	R57E
$\frac{1}{4}$ S 20	
S 29	

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.

TOWNSHIP 44 NORTH, RANGE 57 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by T.H. Lowe, U.S. Deputy Surveyor, in 1900.

Bearings were determined by compass using a magnetic declination of $18\frac{1}{2}^{\circ}$ east.

The cor. of secs. 22, 23, 26 and 27, monumented with a quartzite stone, 15x9x5 ins., firmly set in a mound of stone, mkd. with 2 notches on the S. and E. edges.

At the corner point