

TOWNSHIP 43 NORTH, RANGE 59 EAST, MDM, NEVADA

CHAINS

TOWNSHIP 43 NORTH, RANGE 59 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by Maxson and Gignoux, U.S. Deputy Surveyors, in 1897.

The cor. of secs. 3, 4, 9 and 10, monumented with a volcanic stone, 20x14x4 ins., firmly set 15 ins. in the ground, mkd. with 5 notches on the S. edge and 3 notches on the E. edge, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T43N R59E
S 4 S 3
S 9 S 10

1975

deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located 14 lks. N. of an E-W fence.

The ¼ sec. cor. of secs. 3 and 10, monumented with a volcanic stone, 14x9x6 ins., firmly set 9 ins. in the ground, mkd. ¼ on N. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T43N R59E
¼ S 3
¼ S 10

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This cor. is located 28 lks. S. of an E-W fence.