

441

## TOWNSHIP 43 NORTH, RANGE 59 EAST, MDM, NEVADA

## CHAINS

The cor. of secs. 4, 5, 8 and 9, monumented with a volcanic stone, 14x10x4 ins. firmly set 9 ins. in the ground, mkd. with 5 notches on the S. edge and 4 notches on the E. edge, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T43N R59E				
S	5		S	4
S	8		S	9

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

The ¼ sec. cor. of secs. 4 and 9, monumented with a volcanic stone, 14x12x5 ins., firmly set 9 ins. in the ground, mkd. ¼ on N. face, with a mound of stone N.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T43N R59E			
¼	S	4	
	S	9	

1975

deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This cor. is located 5 lks. N. of an E-W fence.

## TOWNSHIP 44 NORTH, RANGE 59 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by Maxson and Gignoux, U.S. Deputy Surveyors, in 1897.

The cor. of Tps. 43 and 44 N., Rs. 59 and 60 E., monumented with a volcanic stone, 12x12x10 ins., firmly set 8 ins. in the ground, mkd. with 6 notches on the N., S., E. and W. edges, 44N on NE. face, 60E on SE. face, 43N on SW. face and 59E on NW. face.

At the corner point