

TOWNSHIP 44 NORTH, RANGE 59 EAST, MDM, NEVADA

CHAINS

The cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a volcanic stone, 15x10x8 ins., firmly set 10 ins. in the ground, mkd. with 2 notches on the S. edge and 4 notches on the N. edge, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T44N
R59E R60E
S 24 | S 19
S 25 | S 30

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located 6 lks. E. of a N-S fence.

The cor. of secs. 23, 24, 25 and 26, monumented with a volcanic stone, 16x8x6 ins., firmly set 11 ins. in the ground, mkd. with 2 notches on the S. edge and 1 notch on the E. edge, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T44N R59E
S 23 | S 24
S 26 | S 25

1975

deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

The ¼ sec. cor. of secs. 23 and 26, monumented with a volcanic stone, 14x8x8 ins., firmly set 9 ins. in the ground, mkd. ¼ on N. face, with a mound of stone N.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T44N R59E
¼ S 23
¼ S 26

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.