

TOWNSHIP 44 NORTH, RANGE 59 EAST, MDM, NEVADA

CHAINS

The cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp. monumented with a volcanic stone, 12x9x5 ins., firmly set 8 ins. in the ground, mkd. with 2 notches on the E. edge and 4 notches on the W. edge, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T44N R59E
 S 34 | S 35
 S 3 | S 2
 T43N

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

TOWNSHIP 37 NORTH, RANGE 60 EAST, MDM, NEVADA

These field notes are those of a Remonumentation of Certain Corners of the Survey Executed by C.C. Tracy, U.S. Deputy Surveyor, in 1869, and Resurveyed by H. Thurtell, U.S. Deputy Surveyor, in 1904.

The cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a granite stone, 18x10x5 ins., firmly set 12 ins. in the ground, mkd. with 4 grooves on the N. face and 2 grooves on the S. face, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N
 R60E R61E
 S 24 | S 19
 S 25 | S 30

1975

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located 6 lks. E. of a N-S fence.