

TOWNSHIP 27 NORTH, RANGE 56 EAST, MDM, NEVADA

CHAINS

These field notes are those of the Remonumentation of Certain Corners of the Survey Executed by Lee G. B. McDowell, U.S. Deputy Surveyor, in 1904.

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with a conglomerate stone, 18x10x6 ins., firmly set 6 ins. in the ground, mkd.  $\frac{1}{4}$  on the N. face, with a mound of stone N.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T27N R56E  
 $\frac{1}{4}$  S 35  
S 2  
T26N

1971

deposit the original cornerstone alongside the iron post.

rebuild the mound of stone, 4 ft. base, 3 ft. high, N. of cor.

The  $\frac{1}{4}$  sec. cor. of secs. 34 and 35, monumented with a limestone, 15x10x5 ins., firmly set 5 ins. in the ground, mkd.  $\frac{1}{4}$  on the W. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T27N R56E  
 $\frac{1}{4}$   
S 34 | S 35

1971

deposit the original cornerstone alongside the iron post.

set a steel fence post, 6 ft. long, alongside the iron post.

TOWNSHIP 30 NORTH, RANGE 57 EAST, MDM, NEVADA

These field notes are those of the Remonumentation of Certain Corners of the Survey Executed by William T. Moran, U.S. Deputy Surveyor, in 1890.