

## TOWNSHIP 30 NORTH, RANGE 57 EAST, MDM, NEVADA

CHAINS

T30N R57E  
 S 18 | S 17  
 S 19 | S 20

1971

deposit the original cornerstone alongside the iron post.  
 rebuild the mound of stone, 3 ft. base, 2 ft. high,  
 W. of cor.

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, monumented with a  
 granite stone, 18x12x10 ins., firmly set 6 ins. in the  
 ground, mkd.  $\frac{1}{4}$  on W. face, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins.  
 in the ground to solid rock, and in a mound of stone,  
 3 ft. base to top, with brass cap mkd.

T30N R57E  
 $\frac{1}{4}$   
 S 18 | S 17

1971

deposit the original cornerstone alongside the iron post.

## TOWNSHIP 14 NORTH, RANGE 65 EAST, MDM, NEVADA

These field notes are those of the Remonumentation of  
 Certain Corners of the Surveys Executed by Monroe and  
 Bateman, U.S. Deputy Surveyors, in 1874 and 1875.

Bearings were determined by compass using a magnetic  
 declination of  $17\frac{1}{2}^{\circ}$  E.

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, on the S. bdy. of the  
 Tp., monumented with a limestone, 14x12x11 ins., firmly  
 set in a mound of stone, mkd.  $\frac{1}{4}$  on N. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
 in the ground and in a collar of stone, with brass cap  
 mkd.

T14N R65E  
 $\frac{1}{4}$   $\frac{S 33}{S 4}$   
 T13N

1971

deposit the original cornerstone alongside the iron post.