

## TOWNSHIP 14 NORTH, RANGE 65 EAST, MDM, NEVADA

## CHAINS

from which

A juniper, 7 ins. diam., bears N.  $46^{\circ}$  E.,  
29 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

A pinon, 18 ins. diam., bears S.  $38^{\circ}$  W.,  
21 lks. dist., mkd.  $\frac{1}{4}$  S4 BT.

The cor. of secs. 4, 5, 32 and 33, on the S. bdy. of  
the Tp., monumented with a limestone, 14x8x6 ins., firmly  
set in a mound of stone, mkd. with 4 notches on E. edge  
and 2 notches on W. edge.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T14N R65E	
S 32	S 33
S 5	S 4
T13N	

1971

deposit the original cornerstone alongside the iron post.

raise a mound of stone, 3 ft. base, 2 ft. high, W. of  
cor.

from which

A juniper, 8 ins. diam., bears N.  $20^{\circ}$  E.,  
52 lks. dist., mkd. T14N R65E S33 BT.

A juniper, 9 ins. diam., bears S.  $49^{\circ}$  E.,  
26 lks. dist., mkd. T13N R65E S4 BT.

A juniper, 10 ins. diam., bears S.  $65^{\circ}$  W.,  
118 lks. dist., mkd. T13N R65E S5 BT.

There are no other suitable bearing trees  
available.

The cor. of secs. 15, 16, 21 and 22, monumented with a  
limestone, 16x12x10 ins., firmly set in a mound of  
stone, mkd. with 3 notches on S. and E. edges.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.