

## TOWNSHIP 44 NORTH, RANGE 56 EAST

## CHAINS

These field notes are those of a remonumentation of certain corners on the Ruby Valley Guide Meridian of the survey executed by Dennis Scully, U. S. Deputy Surveyor, in 1896, and partially retraced by Newton E. Potter, U.S. Surveyor, in 1915.

The 1896  $\frac{1}{4}$  sec. cor. of sec. 18, now an angle point, on the W. bdy. of the Tp., monumented with a limestone, 16x16x8 ins., firmly set and plainly mkd.  $\frac{1}{4}$  on the E. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T44N  
R55E R56E  
AP  
S 13 | S 18

1967

bury the corner stone alongside the iron post.

This cor. is located on a steep rocky N. slope.

The 1896 cor. of secs. 7 and 18, now an angle point, on the W. bdy. of the Tp., monumented with a limestone, 20x20x8 ins., firmly set and plainly mkd. 4 grooves on the S. face and 2 grooves on the N. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T44N  
R55E R56E  
AP  
S 13 | S 18

1967

bury the corner stone alongside the iron post.

This cor. is located in a fence, bearing N. and S.

The 1896  $\frac{1}{4}$  sec. cor. of sec. 7, now an angle point, on the W. bdy. of the Tp., monumented with a limestone, 14x8x6 ins., firmly set and plainly mkd.  $\frac{1}{4}$  on the E. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.