

TOWNSHIP 44 NORTH, RANGE 56 EAST

CHAINS

T44N
R55E R56E
AP
S 12 | S 7

1967

bury the corner stone and set an aluminum fence post alongside the iron post.

This cor. is located in a fence, bearing N. and S.

The 1896 cor. of secs. 6 and 31, Tps. 44 and 45 N., R. 56 E., now an angle point, monumented with a granite stone, 14x10x6 ins., firmly set and plainly mkd. 6 notches on N. and S. edges and R. 56 E. on E. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T44N
R55E R56E
AP
S 1 | S 6

1967

bury the corner stone and set a steel fence post alongside the iron post.

This cor. is located on a rocky E. slope.

These field notes are those of a remonumentation of certain corners of the survey executed by George S. Nickerson, U. S. Deputy Surveyor, in 1906.

The ¼ sec. cor. of secs. 1 and 2, monumented with a lava stone, 14x8x8 ins., firmly set and plainly mkd. ¼ on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T44N R56E
¼
S 2 | S 1

1967

bury the corner stone and set an aluminum fence post alongside the iron post.