

TOWNSHIP 45 NORTH, RANGE 56 EAST

CHAINS

bury the corner stone and set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

This cor. is located on a steep SSE. slope.

The 1896 $\frac{1}{4}$ sec. cor. of sec. 7, now an angle point, on the W. bdy. of the Tp., monumented with a limestone, 14x8x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the E. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T45N
R55E R56E
AP
S 12 | S 7

1967

bury the corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on a steep SE. slope.

The 1896 cor. of secs. 6 and 7, now an angle point, on the W. bdy. of the Tp., monumented with a lava stone, 16x12x8 ins., firmly set and plainly mkd. 5 notches on the S. edge and 1 notch on the N. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T45N
R55E R56E
AP
S 12 | S 7

1967

bury the corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on the W. end of a spur sloping W.

The 1896 $\frac{1}{4}$ sec. cor. of sec. 6, now an angle point, on the W. bdy. of the Tp., monumented with a lava stone, 16x8x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the E. face.

At the corner point