

TOWNSHIP 45 NORTH, RANGE 56 EAST

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T45N
R55E R56E
AP
S 1 | S 6

1967

bury the corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on a steep rocky N. slope.

The closing cor. of secs. 1 and 6, T. 45 N., Rs. 55 and 56 E., on the Ruby Valley Guide Meridian, monumented with a lava stone, 16x8x8 ins., firmly set and plainly mkd. 6 notches on the E., W. and S. edges and CC on the S. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T46N R55E
S 1 | S 6
T45N
R55E R56E
CC

1967

bury the corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 3 ft. high, S. of cor.

These field notes are those of a remonumentation of certain corners of the survey executed by George A. Bellinger, U. S. Deputy Surveyor, in 1904, and retraced by George S. Nickerson, U. S. Deputy Surveyor, in 1906.

The cor. of secs. 35 and 36 on the S. bdy. of the Tp., monumented with a granite stone, 14x10x6 ins., mkd. 1 notch on the E. edge and 5 notches on the W. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T45N R56E
S 35 | S 36
S 2
T44N

1967