

TOWNSHIP 45 NORTH, RANGE 56 EAST

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T45N R56E
 $\frac{1}{4}$ $\frac{S \ 32}{S \ 5}$
 T44N

1967

bury the corner stone and set an aluminum fence post alongside the iron post and raise a mound of stone, 3 ft. base and 2 ft. high, N. of cor.

This cor. is located on an E. slope.

The cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., monumented with a granite stone, 18x10x10 ins., firmly set and plainly mkd. 5 notches on the E. edge and 1 notch on the W. edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T45N R56E
 $\frac{S \ 31 \ | \ S \ 32}{S \ 6 \ | \ S \ 5}$
 T44N

1967

bury the corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on top of a ridge bearing N. and S.

The closing cor. of secs. 6 and 31, Tps. 44 and 45 N., R. 56 E., monumented with a granite stone 14x8x8 ins., mkd. 6 notches on the S. and E. edges and CC on the E. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T44N T45N
 R55E R56E
 S 1 $\frac{S \ 31}{S \ 6}$ CC
 T44N

1967