

TOWNSHIP 45 NORTH, RANGE 56 EAST

CHAINS

T45N R56E
 $\frac{1}{4}$ $\frac{S 29}{S 32}$

1967

bury the original corner stone and set an aluminum fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This cor. is located in rolling meadow land.

The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a limestone, 16x12x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T45N R56E
 $\frac{1}{4}$ $\frac{S 30}{S 31}$

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on a steep grassy NW. slope.

The closing cor. of secs. 30 and 31, T. 45 N., R. 56 E., monumented with a limestone, 16x10x8 ins., firmly set and plainly mkd. 5 notches on the N. edge, 1 notch on the S. edge and CC on the E. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T45N
 R55E R56E
 $S 36 \left| \frac{S 30}{S 31} \right. CC$

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on a SE. slope.