

## TOWNSHIP 45 NORTH, RANGE 56 EAST

## CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T45N	R56E
S 6	S 5
S 7	S 8

1967

bury the original corner stone alongside the iron post.

This cor. is located on a steep NW. slope about 2.00 chs. distance N. of a grove of aspens.

The closing cor. of secs. 6 and 7, T. 45 N., R. 56 E., monumented with a lava stone, 24x8x8 ins., firmly set and plainly mkd. 1 notch on the N. edge, 5 notches on the S. edge and CC on the E. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T45N	
R55E	R56E
S 12	S 6
	S 7
	CC

1967

bury the original corner stone and set an aluminum fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

This cor. is located at the bottom of a draw and 1.50 chs. W. of a trail road bearing NE. and SW.

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, monumented with a granite stone, 16x14x6 ins., firmly set and plainly mkd.  $\frac{1}{4}$  on the W. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T45N	R56E
$\frac{1}{4}$	
S 6	S 5

1967