

## TOWNSHIP 44 NORTH, RANGE 55 EAST

CHAINS

T44N  
R54E R55E  
 $\frac{1}{4}$   
S 1 | S 6

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on an E. slope at the W. end of a grove of aspens.

The cor. of secs. 13, 14, 23 and 24, monumented with a quartzite stone, 20x14x14 ins., firmly set and plainly mkd. 3 grooves on the S. face and 1 groove on the E. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T44N R55E  
S 14 | S 13  
S 23 | S 24

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.

This cor. is located in a fence, bearing E. and W.

The closing cor. of secs. 13 and 24, T. 44 N., R. 55 E., monumented with a limestone, 16x14x10 ins., firmly set and plainly mkd. 3 notches on the N. and S. edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T44N  
R55E R56E  
CC S 13 | S 18  
S 24 |

1967

bury the original corner stone alongside the iron post.

This cor. is located on a very steep N. slope.

The ¼ sec. cor. of secs. 14 and 23, monumented with a quartzite stone, 18x12x8 ins., firmly set and plainly mkd. ¼ on the N. face.