

TOWNSHIP 44 NORTH, RANGE 55 EAST

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T44N R55E} \\ \frac{1}{4} \text{ S } 14 \\ \hline \text{S } 23 \end{array}$$

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on the W. side of a ridge, bearing N. and S.

The closing cor. of secs. 2 and 3, on the N. bdy. of the Tp., monumented with a granite stone, 24x14x8 ins., firmly set and plainly mkd. 2 grooves on the E. face, 4 grooves on the W. face and CC on the S. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

$$\begin{array}{r} \text{T45N R55E} \\ \text{S } 34 \\ \hline \text{S } 3 \mid \text{S } 2 \\ \text{T44N R55E} \\ \text{CC} \end{array}$$

1967

bury the original corner stone and set a steel fence post alongside the iron post.

This cor. is located on a grassy S. slope.

The ¼ sec. cor. of secs. 21 and 22, monumented with a conglomerate stone, 18x8x6 ins., firmly set and plainly mkd. ¼ on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T44N R55E} \\ \frac{1}{4} \\ \text{S } 21 \mid \text{S } 22 \end{array}$$

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.