

TOWNSHIP 44 NORTH, RANGE 55 EAST

CHAINS

bury the original corner stone and set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located on a gentle SE. slope.

The cor. of secs. 9, 10, 15 and 16, monumented with a quartzite stone, 15x10x10 ins., firmly set and plainly mkd. 4 notches on the S. edge and 3 notches on the E. edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T44N	R55E
S 9	S 10
S 16	S 15

1967

bury the original corner stone and set a steel fence post alongside the iron post.

This cor. is located on a N. slope.

The ¼ sec. cor. of sec. 3 and 4, monumented with a lava stone, 16x13x4 ins., firmly set and plainly mkd. ¼ on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T44N	R55E
S 4	S 3

1967

bury the original corner stone and set an aluminum fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

The closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., monumented with a quartzite stone, 15x8x7 ins., firmly set and plainly mkd. 3 grooves on the E. and W. faces and CC on the S. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.