

491

## TOWNSHIP 45 NORTH, RANGE 55 EAST

## CHAINS

bury the original corner stone and set a steel fence post alongside the iron post.

This cor. is located on a grassy S. slope.

The  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, monumented with a limestone, 16x8x6 ins., firmly set and plainly mkd.  $\frac{1}{4}$  on the W. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T45N R55E

$\frac{1}{4}$   
S 35 | S 36

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on a steep NE. slope.

The cor. of secs. 25, 26, 35 and 36, monumented with a limestone, 16x10x8 ins., firmly set and plainly mkd. 1 groove on the S. and E. faces.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T45N R55E

S 26 | S 25  
S 35 | S 36

1967

bury the original corner stone and set an aluminum fence post alongside the iron post.

This cor. is located on a grassy W. slope.

The closing cor. of secs. 25 and 36, T. 45 N., R. 55 E., monumented with a limestone, 16x12x8 ins., firmly set and plainly mkd. 1 notch on the S. edge, 5 notches on the N. edge and CC on the W. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.