

TOWNSHIP 45 NORTH, RANGE 55 EAST

CHAINS

bury the original corner stone and set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

This cor. is located on a NE. slope.

TOWNSHIP 46 NORTH, RANGE 61 EAST
MOUNT DIABLO MERIDIAN, NEVADA

These field notes are those of a remonumentation of certain corners of the survey executed by H. B. Maxson, U. S. Deputy Surveyor, in 1899.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a lava stone, 16x8x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to underlying rock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.

T46N
R61E R62E
 $\frac{1}{4}$
S 12 | S 7
1967

bury the original corner stone alongside the iron post.

This cor. is located on the S. edge of a draw draining ENE.

The cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a lava stone, 18x10x8 ins., firmly set and plainly mkd. 5 notches on the S. edge and 1 notch on the N. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T46N
R61E R62E
S 1 | S 6
S 12 | S 7
1967

bury the original corner stone alongside the iron post.

This cor. is located on a S. slope, in a fence which bears N. and S. and 80 lks. N. of a gate in the fence.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with a lava stone, 28x20x20 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the W. face.

At the corner point