

TOWNSHIP 46 NORTH, RANGE 61 EAST

CHAINS

bury the original corner stone alongside the iron post.

This cor. is located on a steep grassy NW. slope, 80 lks. from top of spur sloping NE.

The cor. of secs. 13, 14, 23 and 24, monumented with a lava stone, 18x14x6 ins., firmly set and plainly mkd. 3 notches on the S. edge and 1 notch on the E. edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to underlying rock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T46N	R61E
S 14	S 13
S 23	S 24

1967

bury the original corner stone alongside the iron post.

This cor. is located on a gentle grassy S. slope about 4.00 chs. N. of Elk Springs.

The ¼ sec. cor. of secs. 13 and 14, monumented with a lava stone, 14x10x3 ins., firmly set and plainly mkd. ¼ on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4½ ft. base, with brass cap mkd.

T46N	R61E
S 14	S 13

1967

bury the original corner stone alongside the iron post.

The cor. is located on the N. edge of a low grassy ridge bearing E. and W.

The cor. of secs. 11, 12, 13 and 14, monumented with a lava stone, 16x8x3 ins., firmly set and plainly mkd. 4 notches on the S. edge and 1 notch on the E. edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 3½ ft. base, with brass cap mkd.