

Limited Dependent Resurvey,
T. 32 S., R. 66 E., M. D. M., Nevada

Chains	
	T32S R66E S C <u>$\frac{1}{4}$ S 32</u> T33S 1961
51.85	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground, embedded in concrete, for witness meander cor. of secs. 32 and 5, with brass cap mkd. T32S R66E S32 WC <u>S5</u> MC T33W 1961
52.85	Right bank of Colorado River, bearing N. $84^{\circ} 43'$ E. and S. $63^{\circ} 53'$ W., and true point for meander cor. of secs. 5 and 32. The point falls on a steep bank where a monument cannot be maintained. Set the witness cor. as described above. Land, rolling W. 24 chs.; level E. 29 chs. Soil, shallow sandy loam on $W\frac{1}{2}$; sandy silt on $E\frac{1}{2}$. Timber, mesquite and willow in $E\frac{1}{2}$. Undergrowth, scattered cacti and creosote bush in $W\frac{1}{2}$; dense arrowweed in $E\frac{1}{2}$.
<div>Dependent Resurvey of a Portion of the Subdivision Lines, T. 32 S., R. 66 E., M. D. M.</div> <div>Reestablishment of the Surveys and Resurveys executed by T. A. Magee, Deputy Surveyor, in 1883, and J. W. Hardison, Cadastral Engineer, in 1947.</div>	
	From the standard cor. of secs. 31 and 32, on S. bdy. of Tp., hereinbefore described. Thence N. $0^{\circ} 20'$ E., bet. secs. 31 and 32. Over gently sloping land, in bottom of ravine.
2.50	Wash, 1 ch. wide, 2 ft. deep, drains E.
4.00	Base of rugged hills, bears E. and W.; asc. 150 ft. over S. slope.
16.60	Transmission line, bears N. 80° E. and S. 80° W., on crest of ridge; descend 60 ft. over N. slope.
26.90	Wash, 30 lks. wide, 2 ft. deep, drains E.; asc. 40 ft. over S. slope.
31.90	Spur, slopes SE.; desc. 30 ft. over NE. slope.
34.70	Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. 100 ft. over SW. slope.
38.88	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, which is marked by a granite stone, 14 x 12 x 6 ins., mkd. $\frac{1}{4}$ on W. face, conforming to the original record.