

Township 18 South, Range 55 East

Chains

The following data is set forth for a report on the investigation which was made on a portion of the original rectangular survey in T. 18 S., R. 55 E.

The east boundary of the township was surveyed under Contract No. 31, by E. B. Monroe, in 1869, as represented on the plat approved October 14, 1881.

The north, south, and west boundaries, and the subdivisional lines were surveyed under Contract No. 114, by Theodore Binge, in 1881, as represented on the plat approved October 14, 1881.

The south boundary of secs. 31 and 32, (north boundary of secs. 5 and 6, T. 19 S., R. 55 E.), were dependently resurveyed under Group No. 186, Nevada, by Wilson McConkie, in 1942, as shown on the plat approved December 3, 1956.

The investigation was requested by the State Director, for the remonumentation of identified original corners for control for the boundaries of the National Land Reserve, and to assist in the management and fire rehabilitation in the Wheeler Pass burn in the township.

The investigation consisted of a projection of a traverse line from the original $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the N. bdy. of the township, thence S-S-W., through secs. 2, 3, 10, 15, 16, 21, 28, 29, and 32, to the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on the S. bdy. of the township.

Before restoring the corners, a diligent search was made for evidence of a number of the original corners, bearing trees, and/or other calls of the original field note record.

Where the original corner position was duly identified, the corner positions were remonumented and accessories noted, and/or added, and are reported hereinafter.

Remonumentation of Corners - T. 18 S., R. 55 E., M.D. Mer.

The cor. of secs. 29, 30, 31, and 32, T. 18 S., R. 55 E., which is marked by a wooden post, 4 ins. sq. at top, 24 ins. above ground, firmly set in ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to solid rock, and in a collar of stone to top, with brass cap mkd.

T18S R55E	
S 30	S 29
S 31	S 32
1962	

from which

The original bearing trees were identified and recorded

A juniper, 24 ins. diam., bears N. $52^{\circ} 00'$ E., 58 lks. dist., marked as described in the official record. (The record).

A juniper, 16 ins. diam., bears S. $51^{\circ} 15'$ W., 20 lks. dist., marked as described in the official record. (Record, S. 51° W., 20 lks.).

Reset the original corner post, alongside the iron post.