

Remonumentation of Corners - T. 18 S., R. 55 E., M. D. Mer.

Chains

The cor. of secs. 21, 22, 27, and 28, which is marked by the remains of a mound of earth and collar of stone, and substantiated by ties to the original bearing trees

A pinon, 18 ins. diam., bears N. 44° 00' E., 96 lks. dist., mkd. as described in the official record. (Record).

A pinon, 10 ins. diam.; bears S. 72° 00' E., 94 lks. dist., mkd. as described in the official record. (Record).

A pinon, 12 ins. diam., bears S. 74° 00' W., 186 lks. dist., mkd. as described in the official record. (Record).

At the corner point

Set an iron post, 28 ins. long, 8 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T18S R55E
S 21 | S 22
S 28 | S 27
1962

The ¼ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., which is marked by a granite stone, 30x20x10 ins., above ground, firmly set in ground, marked ¼ on N. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T17S R55E
S 35
¼ —————
S 2
T18S
1962

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

Reset the marked stone, alongside the iron post.

The cor. of Tps. 17 and 18 S., Rs. 55 and 56 E., which is marked by a granite stone, 30x15x6 ins., above ground, firmly set in ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S
R55E R56E
S 36 | S 31
S 1 | S 6
T 18 S
1962

Raise a mound of stone, 4½ ft. base, 2½ ft. high, S. of cor.

Reset the marked stone, alongside the iron post.