2

CHAINS

Dependent Resurvey of the South Boundary T. 43 N., R. 32 E., Mount Diablo Mer., Nevada

Reestablishment of the Survey Executed by Skinner, Garside and Preble, Deputy Surveyors, in 1873

The cor. of Tps. 42 and 43 N., Rs. 32 and 33 E., monumented with an unmarked stone, 12x8x6 ins., firmly set in a mound of stone.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of cap, with brass cap mkd.

T43N R32E R33E S 36 S 31 S 1 S 6 T42N 1962

Bury the original corner stone alongside the iron post.

N. 88° 57' W., bet. secs. 1 and 36.

Over rolling land, through medium undergrowth; desc. 350 ft. over W. slope of ridge.

20.80 Base of steep descent, bears N. and S.; desc. 40 ft. over gradual W. slope.

The ½ sec. cor. of secs. 1 and 36, monumented with a rock in place, 3x2x2 ft. above ground, mkd. ½ on top S. edge.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of cap, with brass cap mkd.

T43N R32E

1/4 S 36

S 1

T42N
1962

Iron post set along the east side of the corner stone.

N. 88° 55' W., beginning new measurement.

Over gentle W. slope; desc. 40 ft.

40.15 Point for the cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T43N R32E S 35 S 36

> T42N 1962

Land, rolling to gently rolling. Soil, sandy clay. Undergrowth, sagebrush, greasewood and shadscale.