

CHAINS

- 38.60 Fence, 4 strand barb-wire, bears N. and S.
- 40.33 The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented with an unmarked woodpost, 1x1x15 ins., loosely set, alongside a 4 in. square, 6 ft. long, woodpost, firmly set.
- At the corner point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.
- T43N R32E
 $\frac{1}{4}$ S 17
S 20
1962
- Reset original woodpost and 4 ins. square, 6 ft. long, woodpost alongside iron post.
-
- N. $88^{\circ} 27'$ W., beginning new measurement.
- Over nearly level land.
- 30.50 Drainage ditch, 10 lks. wide, drains SW. into pond.
- 35.00 Asc. 33 ft. over E. slope of small ridge.
- 39.23 The cor. of secs. 17, 18, 19 and 20.
- Land, nearly level.
Soil, sandy clay.
cleared land, 15.00 chs.
Alfalfa, 19.10 chs.
Undergrowth, sagebrush and alfalfa.
-
- N. $87^{\circ} 21'$ W., bet. secs. 18 and 19.
- Over gently rolling land, through medium undergrowth.
- 2.00 Small spur, bears S.
- 11.80 Old Highway 8A, bears S. 10° E. and N. 10° W.
- 14.10 R.E.A. powerline, bears S. $39^{\circ} 12'$ E. and N. $39^{\circ} 12'$ W.
- 18.30 Nevada State Highway 8A, bears S. $39^{\circ} 12'$ E. and N. $39^{\circ} 12'$ W.
- 37.80 Gravel road, bears S. 60° E. and N. 60° W.
- 40.24 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.
- T43N R32E
 $\frac{1}{4}$ S 18
S 19
1962
- 70.70 Trail road, bears S. 10° E. and N. 10° W.
- 78.86 The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., an iron post, $2\frac{1}{2}$ ins. diam., set, marked, and witnessed as described in the field notes of the concurrent resurvey of T. 43 N., R. 31 E.