6

CTTATAT	•	
CHAIN	2	

40.08

The cor. of secs. 5, 6, 31 and 32, monumented with the remains of the original wood post. There are no legible scribe markings.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

Reset the original wood post alongside the iron post.

Land, gently rolling. Soil, sandy clay.

Undergrowth, sagebrush, shadscale and greasewood.

N. 89° 24' W., bet. secs. 6 and 31.

Over gently rolling land, through medium undergrowth.

Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

58.00 Wash, 60 lks. wide, 2 ft. deep, drains S. 20° W.

61.70 Graded dirt road, bears N. 20° E. and S. 20° W.

79.17 The cor. of Tps. 44 and 45 N., Rs. 30 and 31 E., at proportionate distances; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

Reset the original wood post alongside the iron post.

From this point, the cor. of secs. 1, 2, 35 and 36, Tps. 44 and 45 N., R. 30 E., monumented with an iron post, 2 ins. diam., set, mkd., and witnessed as described in the official record, bears N. 89° 18' W., 80.23 chs. distance

From the same point, the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, T. 45 N., Rs. 30 and 31 E., monumented with a squared wood post, 1x1x30 ins. long, bears N. 2° 09' W., 40.21 chs. distance.

At the corner point