

CHAINS

N. 89° 43' W., beginning new measurement.

Over nearly level land.

40.00 Point for the cor. of secs. 5, 6, 31 and 32, at record distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T43N	R31E
<u>S 31</u>	<u>S 32</u>
S 6	S 5
T42N	
1962	

Land, nearly level.

Soil, sandy clay.

Undergrowth, sagebrush and shadscale.

N. 89° 43' W., bet. secs. 6 and 31.

Over gently rolling land, through medium undergrowth.

26.30 Wash, 10 lks. wide, 2 ft. deep, drains S.

30.40 Trail road, bears N. and S.

40.00 Point for the ¼ sec. cor. of secs. 6 and 31, at record distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T43N	R31E
¼ <u>S 31</u>	
S 6	
T42N	
1962	

42.30 Gravel road, bears N. and S; asc. 250 ft. over E. slope.

78.72 Point for the cor. of Tps. 42 and 43 N., Rs. 30 and 31 E., at record distance longitudinally and proportionate distance latitudinally; there is no remaining evidence; of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base, to top of cap, with brass cap mkd.

T43N	
R30E	R31E
<u>S 36</u>	<u>S 31</u>
S 1	S 6
T42N	
1962	