

## DEPENDENT RESURVEY, EAST BDY. T. 41 N., R. 27 E. 2

CHAINS

Dependent Resurvey of the East Bdy.  
T. 41 N., R. 27 E., Mount Diablo Meridian  
Nevada

Reestablishment of the Survey Executed  
by Skinner, Garside and Preble, Deputy Surveyors  
and partially retraced by E. Voight in 1922.

Beginning at the cor. of secs. 13, 18, 19 and 24, on  
the E. bdy. of the Tp., monumented with an iron post,  
3 ins. diam., set, mkd. and witnessed as described in  
the official record.

N. 2° 03' W., bet. secs. 13 and 18.

Over rolling land, through sparse undergrowth.

5.40 Spur, bears NE., desc. 270 ft. over NE. slope.

25.40 Small ravine, drains E.; continue along E. slope.

30.20 Ravine, drains E., continue along rolling E. slope.

40.47 The  $\frac{1}{2}$  sec. cor. of secs. 13 and 18, monumented with a  
stone, 16x6x6 ins., firmly set in a mound of stone, and  
plainly mkd. with  $\frac{1}{2}$  on the W. face.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 5 ins.  
in the ground to bedrock and in a mound of stone, 5 ft.  
base, to cap, with brass cap mkd.

T41N  
R27E R28E  
 $\frac{1}{2}$   
S 13 | S 18  
1962

Bury the original corner stone alongside the iron post.

N. 0° 37' E., beginning new measurement.

Over rolling land.

0.30 Ravine, drains SE., asc. 240 ft. over SW. slope.

11.50 Top of ascent slopes SW., desc. 170 ft. along W. slope.

40.60 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E.,  
continue over rolling land.

41.92 The cor. of secs. 7, 12, 13 and 18, monumented with a  
stone 24x12x7 ins., plainly mkd. with 6 notches on the  
E. face and 4 notches on the S. face.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.