

CHAINS	
60.00	Begin ascent over E. slope of Bartlett Butte; asc. 180 ft.
69.50	Ravine, drains S. 70° E. from W.
71.00	Leave ravine, drains E. from S. 70° W.; asc. 210 ft. over steep E. slope.
83.93.	Point for the cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.  <div style="text-align: center;"> T42N R 27 E  <hr/> S 35   S 36  1962 </div> Land, rolling to mountainous. Soil, sandy clay. Undergrowth, sagebrush.
	The cor. of secs. 1 and 12, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the corner.  At the corner point  Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground with the brass cap mkd.  <div style="text-align: center;"> T42N  R27E   T42N  S 1   S 6  S 12 R28E  1962 </div> No available accessories.  from which: The ¼ sec. cor. sec. 6, T. 42N., R. 28E., an iron post, 1 in. diam., set, mkd., and witnessed as described in the official record, bears N. 0° 10' E., 29.85 chs. dist.  The cor. of secs. 6 and 7, T. 42 N., R. 28E., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, bears S. 0° 10' W., 10.15 chs. dist.  S. 85° 50' W., bet. secs. 1 and 12.  Over nearly level meadow land, through medium undergrowth.
26.00	Barb-wire fence, bears N. 15° E. and S. 15° W.
40.255	Point for the ¼ sec. cor. of secs. 1 and 12, at record distance; there is no remaining evidence of the original corner.  Set an iron post, 30 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> T42N R27E  ¼ S 1  S 12  1962 </div>