

DEPENDENT RESURVEY, E. Boundary, T. 44 N., R. 27 E. 2

CHAINS

Dependent resurvey of the East boundary, T. 44 N., R. 27 E., Mount Diablo Meridian, Nevada

Re-establishment of the survey executed by Garside & Preble, Deputy Surveyors, in 1873

The corner of Tp. 44 N., R. 27 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam. set and mkd. as described in the field notes of T. 43 N., R. 27 E., resurveyed concurrently with this group.

At the corner point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to cap, with brass cap mkd.

T44 N
R27E
S 36
1962

Bury the original corner alongside the iron post.

N. $0^{\circ} 07'$ W., along the E. bdy. of sec. 36.

Over rolling land, through medium undergrowth; asc. 200 ft. over S. slope.

7.20 Top of ascent; ridge bears NE. and SW.; desc. 410 ft. over N. slope.

44.12 The $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a trapstone $30 \times 16 \times 4$ ins. plainly mkd. with $\frac{1}{4}$ on the W. face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, $4\frac{1}{2}$ ft. base to cap, with brass cap mkd.

T44N
R27E R28E
 $\frac{1}{4}$
S 36
1962

Bury the original corner alongside the iron post.

N. $1^{\circ} 01'$ E., beginning new measurement.

Over rolling land; desc. 70 ft. over NW. slope.

2.60 Ravine, drains NW., asc. 30 ft. over S. slope.

9.10 Spur, projects W.; desc. 80 ft. over N. slope.

16.20 Ravine, drains N. 75° W.; asc. 20 ft. over S. slope.

23.60 Spur, projects W.; desc. 20 ft. over N. slope.

26.80 Ravine, drains W.; asc. 5 ft. over S. slope.

33.80 Spur, bears W.; desc. 70 ft. over N. slope.