

CHAINS

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T44N
R27E R28E
 $\frac{1}{2}$ |
S 12 |
1962

Bury the original corner alongside the iron post.

N. $0^{\circ} 40'$ E., beginning new measurement.

Over rolling land.'

- 1.70 Ravine, drains NW., asc. 20 ft. over S. slope.
- 9.80 Spur bears W.; desc. 80 ft. over N. slope.
- 28.40 Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.; asc. 20 ft. over S. slope.
- 30.00 Top of ascent, bear E. and W.; desc. 50 ft. over N. slope.
- 38.20 Trail road, bears E. and SW.
- 41.88 Point for the cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T44N
R27E R28E
S 1 |
S 12 |
1962

Land, rolling.
Soil, sandy clay.
Undergrowth; sagebrush and greasewood.

N. $0^{\circ} 40'$ E., along the E. bdy. of sec. 1.

Desc. gradually over rolling land, through medium undergrowth.

- 4.30 Wash, 20 lks. wide, 1 ft. deep, drains NW.
- 24.60 Wash, 10 lks. wide, 1 ft. deep, drains NW.
- 41.88 Point for the $\frac{1}{2}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.