

CHAINS

Dependent Resurvey, W. bdy., T. 43 N., R. 28 E., Mount
Diablo Meridian, Nevada

Re-establishment of the survey executed by G. W.
Garside, Deputy Surveyor, in 1872.

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a
stone, 12x8x8 ins., firmly set and mkd. $\frac{1}{4}$ on the W. face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43N
R27E R28E
 $\frac{1}{4}$
S 36 | S 31
1962

Bury the original corner stone alongside the iron post
and raise a mound of stone, 4 ft. base, 3 ft. high, W.
of cor.

from which:

The closing corner of Tps. 42 and 43 N., R. 28 E.,
monumented with an iron post, 3 ins. diam., set,
mkd. and witnessed as described in the official
record, bears south 20.84 chs. dist.

N. $1^{\circ} 52'$ E., along the W. bdy. of sec. 31

Over rolling land, along W. slope, through medium under-
growth.

20.70 Cove Creek, 20 lks. wide, 2 ft. deep, course SW.; asc.
90 ft. over S. slope.

31.20 Ravine, drains SW.; asc. 120 ft. over S. slope.

40.73 The cor. of secs. 30 and 31, monumented with a granite
stone, 24x18x10 ins., firmly set in a mound of stone
and mkd. with 5 notches on the N. face and 6 notches
on the W. face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins.
in the ground to bedrock and in a mound of stone to cap,
4 ft. base, with brass cap mkd.

T43N
R27E R28E
| S30
| S31
1962

Bury the original corner stone alongside the iron post.

Land, mountainous
Soil, sandy clay and rocky
Undergrowth, sagebrush.

N. $0^{\circ} 05'$ W., along the W. bdy. of sec. 30.