	DEPENDENT RESURVEY, T. 43 N., R. 29 E. 5
CHAINS	T43N R28E R29E ½ S19 1962
\$ 8 B	Asc 140 ft. over S. slope.
48.30	Ridge, bears E. and W.; desc. 60 ft. over N. slope.
56.60	Ravine, drains N. 50° E.; asc. 290 ft. over S. slope.
68.60	Top of ascent; ridge, bears NE. and SW.; desc. 240 ft. over NW. slope.
80.00	Point for the cor.of sec. 19, at record distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T43N R28E R29E
	S 19 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, SE. cor.
	Land, mountainous. Soil, gravel and sandy clay. Timber, scattered quaken aspen and mahogany. Undergrowth, sagebrush and picklebrush.
	Dependent Resurvey of subdivisional lines, T. 43 N., R. 29 E., Mount Diablo Meridian, Nevada
	Re-establishment of a portion of the survey executed by Skinner, Garside and Preble, Deputy Surveyors, in 1873, and partially retraced by Emil Voight in 1921.
	From the cor. of sec. 31, on the S. bdy. of the Tp.
	N. 1° 03' E., along the E. bdy. of sec. 31.
	Over rolling land, through medium undergrowth; asc. 80 ft. over SE. slope.
14.70	Top of ascent; bears NE. and SW.; desc. 70 ft. over NW. slope.
38.90	Leonard Creek, 10 1ks. wide, 1 ft. deep, course S. 20° W
41.16	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3ft. base to cap, with brass cap mkd.
	T43N R29E
	S 31 S 32 1962
	Asc. 60 ft. over SE. slope.