

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43N	T44N
R29E	R30E
¼	
S 17	
1962	

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner, the cor. of sec. 30 and 31, T. 44 N., R. 30 E. monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, bears south, 15.64 chs. dist. Remarked brass cap to read

T43N	T44N
R29E	R30E
S 17	S 30
	S 31
1918	

From the cor. of secs. 7, 8, 17 and 18.

West, bet. secs. 7 and 18, on record bearing.

Over mountainous land, through medium undergrowth; asc. 120 ft. over E. slope.

- 4.20 Head of spring, course S. 70° E.; asc. 400 ft. over steep E. slope.
- 16.00 Rocky spur, bears SE., asc. 380 ft. over SE. slope.
- 37.70 Rim of rock ledge, bears NE. and SW.; desc. 20 ft. over W. slope.
- 40.00 Point for the ¼ sec. cor. of secs. 7 and 8, at record distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 7 ft. base to cap, with brass cap mkd.

T43N	R29E
¼	S 7
	S 18
1962	

Land, mountainous.
Soil, sandy clay and rocky.
Undergrowth, native grasses and manzanita.

GENERAL DESCRIPTION

The land surveyed within this township is rolling to broken mountains. The soil is sandy clay and rocky.

There are numerous springs and creeks. Leonard Creek drains the area southerly. Principal users of the area are cattlemen and access into the township is provided by trail roads. The timber is composed of quaken aspen along the creeks and scattered mahogany on the higher slopes.

No mineral formations of consequence were noted during the survey.