

Dependent Resurvey of the East Bdy. of T.12N., R.19E.

Chains

deposited at the base, and with brass cap mkd.

T12N	
R19E	R20E
S 1	S 6
S 12	S 7
1939	

Land, level.

Soil, sandy silt loam, 1st to 2nd rate.

Undergrowth, sagebrush, willows.

 N. $0^{\circ}03'$ W., bet. secs. 1 and 6. ($S\frac{1}{2}$ mile.)

Over nearly level cultivated land.

- .18 Wire fence, bears E. and W. 40 lks. to fence line bearing N. and S.
- 15.10 South side of frame house, size 30 ft. by 15 ft. near east end.
- 22.57 Wire fence, bears S. 12° E. and N. 12° W., 50 lks. to cor. from which fences bear N., S. and W.
- 39.47 From this point, fence cor. bears West, 32 lks. dist., fences bear South, West and North.
- 39.61 Power and telephone line, bears N. 64° E. and S. 64° W., 35 lks. thence westerly.
- 39.85 Wire fence, bears N. 65° E., 25 lks. thence E. and S. 65° W., 35 lks. thence S. to fence cor.
- 40.10 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance, in center of east-west lane and mid-distant between old fences on N. and S. sides of lane.
- Set an iron post, 3 ft. long, 1 in. diam., 8 ins. below surface in a large mass of concrete at the base, with brass cap mkd.

$\frac{1}{4}$	
S 1	S 6
1939	

 N. $0^{\circ}03'$ W., bet. secs. 1 and 6. ($N\frac{1}{2}$ mile.)

- .62 Wire fence, bears E. and W.
- 4.50 Shallow slough, 6 lks. wide, drains SW.
- 22.44 Wire fence, bears E. and W. 45 lks. to fence bearing N. and S.
- 40.10 The point for the cor. of Ts. 12 and 13 N., Rs. 19 and 20 E. is in an old east-west fence line at a record distance of 43 lks. west of a north-south fence line.
- At point for cor.
- Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground and in a large mass of concrete at the base, for the cor. of Ts. 12 and 13 N., Rs. 19 and 20 E., with brass cap mkd.